



青 岛 金 凯 电 气 设 备 有 限 公 司
QINGDAO COSINE ELECTRICAL EQUIPMENT CO.,LTD

复 合 针 式 绝 缘 子
POLYMER PIN INSULATOR

NO.	Tpye	Specified Voltage (kV)	Specified bending Load (kN)	Section Height (mm)	Min Arc distance (mm)	Min creepage distance (mm)	Lightning Impulse Withstand (peak value) (KV)	Wet Power Frequence Withstand (effective value) (KV)	Weight (kg)
1	FPQ-10/2.0	10	2.0	215	145	350	90	40	1.2
2	FPQ-10/3.0	10	3.0	252	145	350	90	40	2
3	FPQ-10/4.0	10	4.0	215	145	350	90	40	--
4	FPQ-10/5.0	10	5.0	215	145	350	90	40	--
5	FPQ-20/12.5	20	12.5	380	248	630	170	75	--
6	FPQ-24/11	24	11	300	166	620	170	75	--
7	FPQ-33/12.5	33	12.5	380	248	630	170	75	--

Address: NO.283 Xiao Shan Road, Economic&Technical Development Zone, Qingdao

TEL: +86-532-80986697

FAX: +86-532-80986697

Website: www.cosinelectric.com

Email: info@cosinelectric.com